

Quest PowerHeat CHH 300 Pro



Central Hydronic Heater System

PowerHeat CHH 300 Pro Specifications

Part Number	4031110
Fuel Input	385,000 BTU/hr
Fuel Options	Diesel
Run Time at Full Load	50 Hours
Efficiency	85%
Heat Transfer Fluid	Propylene Glycol
Pump	1 HP
Lifting Hook	1
Operating Temp Range	-30°F to 140°F
Fluid Temperature Range	100°F to 200°F
Fuel Tank Capacity	120 Gallons
Fuel Consumption at Full Load	2.4 Gallons
Hydronic Flow Rate	30 GPM, 1.89 liters/sec
Hydronic Connections	1" ISO 7241 Series B Couplings
Dimensions	72"L x 31"W x 48"H-in 1829L x 787W x 1219H-mm (Cabinet with Fuel Tank)
Weight	800 lbs. / 363 kg (Empty Fuel Tank) 1700 lbs. / 771 kg (Full Fuel Tank)



PowerHeat CHH 300 Pro

ETL Listed



PowerHeat CHH 300 Pro Features:

- 385,000 BTU Capacity
- Stainless Steel and Aluminum Construction
- Atmospherically-Vented HTC Circuit - eliminating the need for Pressure Vessel classification
- Smooth, clean, cold-weather ignition
- Steady burn efficiency
- Combustion by-products (like carbon dioxide and carbon monoxide) are safely vented out of the chimney instead of inside the structure or customer's home
- Gauges and indicators are clearly visible for quick function checks and easy troubleshooting

Quest Accessories:



Quest PowerHeat HFC 100 Pro Hydronic Fan Coils



Engineered Excellence for
Construction Professionals



Specifications subject to change without notice. 09/15



Therma-Stor LLC
4201 Lien Rd
Madison, WI 53704

1-866-933-7486
www.HeatUpBedBugs.com
sales@HeatUpBedBugs.com