

Quest PowerHeat CHH 980 Pro



Central Hydronic Heater

CHH980 Pro Specifications

Part Number	4033030
Heat Input	990,000
Heat Output	822,000
Efficiency	83%
Fuel Input Rate @ Full Load	7.07 GPH
Electrical Requirements	30 amps, 220V Single Phase
Heat Transfer Fluid	Propylene Glycol
Operating Range	-30 to 140
Fluid Temp Range	100-200
Pump	2 - 1 1/2 HP
Hydronic Flow Rate	80 GPM/3.78 liters per sec
Hydronic Connection	3 sets of 1"
Dimensions	98X48X70
Weight	2941 lbs.
Heat	Up to 1400000 cubic feet
Thaw	18000 sq ft
Cure	27000 sq ft
Frost Prevention	18000 sq ft



PowerHeat CHH 980 Pro

ETL Listed



PowerHeat CHH 980 Pro Features:

- 990,000 BTU Capacity
- Stainless Steel and Aluminum Construction
- Atmospherically-Vented HTC Circuit - eliminating the need for Pressure Vessel classification
- Smooth, clean, cold-weather ignition
- Steady burn efficiency
- Combustion by-products (like carbon dioxide and carbon monoxide) are safely vented out of the chimney instead of inside the structure or customer's home
- Gauges and indicators are clearly visible for quick function checks and easy troubleshooting



Engineered Excellence for
Construction Professionals



Specifications subject to change without notice. 07/12



Therma-Stor LLC
4201 Lien Rd
Madison, WI 53704

1-866-933-7486
www.HeatUpBedBugs.com
sales@HeatUpBedBugs.com